



**OFFICE OF THE REGISTRAR**

মহাপুৰুষ শ্ৰীমন্ত শঙ্কৰদেৱ বিশ্ববিদ্যালয়

**MAHAPURUSHA SRIMANTA SANKARADEVA VISWAVIDYALAYA**

[Recognised Under Section 2(f) of UGC Act, 1956]

Srimanta Sankaradeva Sangha Complex, Haladhar Bhuyan Path,  
Kalongpar, Nagaon, PIN-782001, Assam, India

Ref. No.: MSSV/R/59/2015/23220

Dated: 23.05.2023

**Notice Inviting Quotation**

Sealed quotations are invited from registered/ reputed/ experienced parties/ firms for the following listed items/works in connection with construction of Administrative Building of Mahapurusha Srimanta Sankaradeva Viswavidyalaya at Atuatika, Raidongia stating the rates categorically head wise given in the BOQ.

The sealed quotations must reach the office of the undersigned **on or before 12.00 P.M. of 30<sup>th</sup> May, 2023** and the same will be opened on 30<sup>th</sup> May, 2023 at 3.00 P.M. The quotations should accompany with a **Bank Draft of Rs. 2,000.00 (Rupees two thousand) only (non-refundable) payable to the Registrar, Mahapurusha Srimanta Sankaradeva Viswavidyalaya, Nagaon** at State Bank of India, Main Branch, Nagaon (code: 0146).

The following terms and condition must be followed by parties while submitting quotation:

1. Quotation should be submitted in plain paper.
2. Rs. 8.25 court fee stamp should be submitted with quotation.
3. The work allotted party will have to make agreement with the undersigned.
4. The work should be done as per approved drawing and as directed by the undersigned.
5. Payment shall be made on the progress of the work as mentioned in the work agreement.
6. All T & P materials should be managed by the party itself.
7. Detail information may be seen in the University website [www.mssv.ac.in](http://www.mssv.ac.in)

The undersigned reserves the right to accept or reject any quotation without assigning any reason.

(Dr. M. K. Borah)  
Registrar

Date: 23.05.2023

Memo No: MSSV/R/59/2015/23221-26

Copy to:

1. The Secretary to the Hon'ble Vice-Chancellor.
2. The Director (Finance & Planning) cum Chief Co-ordinator for favour of information.
3. The Managing Trustee, SSESED Trust for favour of information.
4. Dr. Santanu Kalita, Asstt. Professor & Head (i/c), Deptt. of Computer Application with a request to upload the notification in the University website [www.mssv.ac.in](http://www.mssv.ac.in).
5. The Assistant Registrar (Finance) for information and necessary action.
6. The Project Engineer for information and necessary action.
7. Notice Board.
8. Office file.

(Dr. M.K. Borah)  
Registrar


**BOQ as per DSR, 2021**

DSR NO.	DESCRIPTION OF ITEM	UNIT	QTTY	RATE IN RS. (AS PER CPWD2021)	QUOTED RATE PER UNIT
	<b>FLOOR, WALL TILE AND GRANITE</b>				
11.41A	Providing and laying Vitrified tiles in floor in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS:15622, of approved brand & manufacturer, in all colours and shade, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) jointing with grey cement slurry @3.3 kg/sqm including grouting the joints with white cement and matching pigments etc. The tiles must be cut with the zero chipping diamond cutter only . Laying of tiles will be done with the notch trowel, plier, wedge, clips of required thickness, leveling system and rubber mallet for placing the tiles gently and easily.				
11.41A.1	Double charge digital vitrified tile polished finish of size	Sqm	956.90	1702.05	
11.41A.1.4	Size of Tile 800 x 1600 mm				
11.41A.3	Glazed Vitrified tiles Matt/Antiskid finish of size				
11.41A.3.2	Size of Tile 600 x 1200 mm	Sqm	38.74	1612.75	
8.31	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	Sqm	119.65	1063.45	
11.55	Providing and laying flamed finish Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building all complete as per the architectural drawings with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement : 4 coarse sand) laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade including rubbing, curing and polishing etc. all complete as specified and as directed by the Engineer-in-Charge :				
11.55.1	Flamed finish granite stone slab Jet Black, Cherry Red, Elite Brown, Cat Eye or equivalent.	Sqm	69.39	2589.90	
	<b>FALSE CEILING</b>				
12.45	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash				

	fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :				
12.45.1	12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) :2011 (Board with BIS certification marks)	Sqm	867.72	1145.95	
	<b>ACOUSTIC CEILING</b>				
12.52.4	12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side, having an NRC (Noise Reduction Coefficient) of 0.79, with 50 mm resin bonded glass wool backing.	Sqm	138.52	1247.50	
	<b>PVC CEILING</b>				
12.52.3	12.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsum plasterboard, manufactured from natural gypsum as per IS 2095 part I and laminated with white 0.16mm thick fire retardant PVC film on the face side and 12micron metalized polyester on the back side with all edges sealed with the face side PVC film which goes around and wraps the edges and is bonded to the edges and the back side metalized polyester film so as to make the tile a completely sealed unit.	Sqm	27	1948.95	
	<b>WOODEN RAFTER CEILING</b>				
7143	Factory made 35 mm thick shutters with laminated veneer lumber styles & rails as per TADS 15:1995	Sqm	67	1910	

	and panels of 12 mm thick one side prelaminate type-I, and other side balancing lamination, medium density flat pressed three layer, graded particle board (FPTI) as per IS:3087 bonded with BWP type synthetic resin adhesive, as per IS:848				
	<b>PUTTY, PRIMER AND PAINT</b>				
13.26	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	Sqm	3346	214.30	
13.43	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : 13.43.1 Water thinnable cement primer	Sqm	3346	64.45	
13.48.A.1	Finishing walls with 100% Premium acrylic emulsion paint having VOC less than 50 gm/litre and UV resistance as per IS 15489:2004, Alkali & fungal resistance, dirt resistance exterior paint of required shade (Company Depot Tinted) with silicon additives. New work (Two or more coats applied @ 1.43 litre/ 10 sqm. Over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm.	Sqm	3346	154.45	
13.48.2	Painting wood work with Deluxe Multi Surface Paint of required shade. Two or more coat applied @ 0.90 ltr/10 sqm over an under coat of primer applied @0.75 ltr/10 sqm of approved brand and manufacture	Sqm	77.59	144.90	
	<b>MAIN DOOR DOUBLE LEAF</b>				
9.20.1	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws. <b>9nos.</b>	Sqm	33.45	3086.10	
	<b>SINGLE DOOR SHUTTER</b>				
	30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws. <b>11 nos.</b>	Sqm	28.62	2818.50	
	<b>TOILET DOOR UPVC/ALUMINIUM 6nos.</b>	Sqm	11.15		
	<b>WINDOW</b>				
9.147D.2	Providing and fixing factory made uPVC white colour sliding glazed window upto 1.50 m in height dimension comprising of uPVC multi-chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to uPVC profile), appropriate dimension of uPVC extruded glazing beads and uPVC extruded interlocks, EPDM gasket, wool pile, zinc alloy (white powder coated) touch locks with hook, zinc alloy body with single nylon rollers (weight bearing capacity to be 40 kg), G.I fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer	Sqm	195	10030.30	

	rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge. (Single / double glass panes, wire mesh and silicon sealant shall be paid separately). Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made. <b>Note:</b> For uPVC frame and sash extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Three track three panels sliding window with fly proof SS wire mesh (Two nos. glazed & one no. wire mesh panels) made of (small series) frame 92 x 44 mm & sash 32 x 60 mm both having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension (Area of window upto 1.75 sqm). 10030.30				
	<b>PARTITION WALL PANELLING</b>				
	Ply wood 7 ply, 9 mm thick . Decorative plywood one side decorative veneer and commercial veneer on other face (Type 1) conforming to IS 1328 BWR Type	Sqm	891.86	2570.70	
	<b>WINDOW GRILL WORK</b> Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes	Kg	234.00	154.90	
	<b>RAILING WORK</b>	Rm	134.00		
	<b>INTERNAL WATER SUPPLY AND SANITARY INSTALLATION CONCEALED</b> (1 COMMON TOILET, 2 ATTACH TOILET),1NO.SEP TIC TANK,200FT DEEP BORE WELL,2NOS. 1000LTR WATER TANK. FOR MORE DETAILS REFER DRAWING)			6,00,000.00	



(Dr. M.K. Borah)  
Registrar

